

IP protected bench scale KERN WTB-N



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]

Features

- **Suitable for the ever-increasing hygienic requirements in the food industry**
- **1 IP65:** Dust and spray protected (only when using rechargeable battery pack)
- Weighing plate stainless steel, removable, for easy cleaning
- **2 Second display** on the rear of the balance
- **Compact size**, practical for small spaces
- **3 Innovative weighing with tolerance range (Checkweighing):** The colour of the display changes depending on the weight (too light/ok/too heavy) and is an aid to help with portioning dosing and grading
- **High mobility** thanks to its rechargeable batteries (optional) and low weight

- **Recessed grips on the underside** of the scale for easy transportation
- Your support in a **HACCP**-compliant quality system

Technical data

- Large backlit LCD display, digit height 25 mm
- Weighing plate dimensions, stainless steel, WxD 260x200 mm
- Overall dimensions WxDxH 280x320x125 mm
- Net weight approx. 3,115 kg
- Permissible ambient temperature -10 °C / 40 °C

Accessories

- **Protective working cover** over keyboard and housing. Can be re-ordered, scope of delivery: 5 items, KERN RFB-A01S05
- **Rechargeable battery pack internal**, operating time up to 50 h, charging time approx. 12 h, can be retrofitted, KERN WTB-A01N
- **4 Tare pan made of stainless steel**, ideal for weighing loose fruit and vegetables, WxDxH 370x240x20 mm, for details see page 182, KERN RFS-A02
- **Sturdy transport case** to protect and store the scale, dimensions WxDxH 510x360x220 mm, for details see page 182, KERN RFB-A02

STANDARD

CAL EXT

UNIT

TOL

IP 65

MULTI

DMS

1

OPTION

ACCU

FACTORY

M

+3 DAYS

Model	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g	Options			
					Verification		DAkkS Calibr. Certificate	
					MID KERN		DAkkS	
WTB 1K-4N	1,5	0,2	–	–	–	–	963-127	
WTB 3K-4N	3	0,5	–	–	–	–	963-127	
WTB 6K-3N	6	1	–	–	–	–	963-128	
WTB 10K-3N	15	2	–	–	–	–	963-128	
WTB 30K-3N	30	5	–	–	–	–	963-128	
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.								
WTB 1K-4NM	1,5	0,5	0,5	10	965-227		963-127	
WTB 3K-3NM	3	1	1	20	965-227		963-127	
WTB 6K-3NM	6	2	2	40	965-228		963-128	
WTB 10K-3NM	15	5	5	100	965-228		963-128	
WTB 30K-2NM	30	10	10	200	965-228		963-128	

KERN Pictograms:

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight.	 Suspended weighing: Load support with hook on the underside of the balance.
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Battery operation: Ready for battery operation. The battery type is specified for each device.
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 Rechargeable battery pack: Rechargeable set.
 Alibi memory: Electronic archiving of weighing results, complying with the 2009/23/EC standard.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode.	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 Data interface RS-232: To connect the balance to a printer, PC or network.		 Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.
 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 USB data interface: To connect the balance to a printer, PC or other peripherals.	 Totalising level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode recognition.	 Weighing principle: Strain gauge Electrical resistor on an elastic deforming body.
 Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.		 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.
 WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.	 Percentage determination: Determining the deviation in % from the target value (100 %).	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings.
 Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision.
 Interface for second balance: For direct connection of a second balance.	 Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.	 Verification possible: The time required for verification is specified in the pictogram.
 Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.	
 Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module.	 Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	
 GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.	 ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.	
 GLP/ISO log: With weight, date and time. Only with KERN printers.	 Stainless steel: The balance is protected against corrosion.	

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAkkS calibration of

balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages D, GB, F, I, E, NL, PL

Your KERN specialist dealer:

