

## Product Specifications

Model number	Cubee 615	
	C-615	C-615V
<b>LCD &amp; Touch Panel</b>		
LCD Panel	15" TFT LVDS	
MAX. Resolution	1024 x 768 (Default)	
Brightness	250 cd/m <sup>2</sup>	
Touch Screen	5-wire Resistive (RS232 type)	
<b>System Configuration</b>		
CPU	Intel Pineview-D D525 1.8GHz (Dual core)	
Chipset	South Bridge: ICH8M	
Main Memory	204-pin DDR3 RAM * 2 slots, up to 4GB	
Graphic Memory	System memory shared up to 224MB	
HDD	1 x 2.5" SATA HDD or SSD (rack-able)	
SATA DOM	Support 1GB to 16GB	
<b>I/O Ports</b>		
Parallel Port	1 x LPT port (optional, cable output)	
Serial Ports	3 x DB-9 COM ports (All with DC 5 / 12V output on Pin 9 selectable) 1 x RJ-45 COM port	
USB Ports	6 x USB 2.0 ports	
LAN Port	1 x (10/100/1000M bps auto)	
Keyboard / Mouse Port	1 x PS/2 keyboard port	
Audio Port	1 x Line out	
VGA Port	1 x DB-15 VGA port	
Cash Drawer Port	1 x RJ-11 port (12V/24V selectable)	
Speaker Output	2 x 1W speaker	
DC Output	1 x DC 12V output	
<b>Powering System</b>		
Power Supply	DC 24V 120W external power supply AC 100V to 240V full range	
Power Button	1 x System on/off switch	
Brightness Control Button	2 x buttons for LCD brightness adjustment	
<b>Physical Dimensions</b>		
Wall mount	N/A	75*75mm VESA standard
Dimension (L x W x D)	329*348*213mm	267*348*75mm
Weight	10Kg	7Kg
<b>Safety &amp; Environment</b>		
Product Certification	CE / FCC /CB/LVD/CCC/BSMI	
Operation Temperature	0°C to 40°C	
Storage Temperature	-25°C to 70°C	
OS Compatibility	Windows XP Pro / Windows 7 / WEPOS/ POSReady 2009 / POSReady 7 / Linux	

Adding flexibility and functionality to POS operation



VFD/LCM  
Customer Display



10.1"/12.1  
2nd LCD Display



3-in-1 reader



Integrates scanner  
(C-615V only)



# Cubee 615

The sleek, powerful and future-proof POS terminal



